

ATA802-BEN-B



About ATA802-BEN-B RFID UHF Antenna

ATID's ATA802-BEN-B antenna is compact RFID UHF Antenna, circular polarization, and the working frequency band is 865MHz~868MHz. Careful design methodology achieves maximum efficiency and performance, with excellent VSWR and axial ratios. It is ideal for many RFID applications such as smart retail, digital warehouse management, logistics management and other fields.

Application

- Smart retail
- Digital warehouse management
- Logistics management and other fields

Features

- Circular polarization
- High performance and high protection
- Beautiful appearance and light weight





Product Specifications

Performance Parameters

Operating Frequency
VSWR
Input Impedance
Gain
Polarization
Connector
HPBW
IP rating

865MHz~868MHz ≤1.5:1 50Ω 5dBi Circular polarization SMA-K type connectors E:100°, H:100° IP65

Environment


Operating Temperature	-40°C to -
Storage Temperature	-40°C to -
Humidity Range	≤95%RH


Physical Parameters

Size Weight Radome material Installation 117.5x117.5x23.5 (mm) 0.16kg Modified ASA Bracket mounting / Screw fastening


+85°C

+85°C





ATA802-BUS-B Type Antenna appearance dimension drawing





All Features and specifications described are subject to change without notice.



Ver 1.0

Partners Tower 1 #1402, 83, Gasan Digital 1-Ro, Geumcheon-gu, Seoul, Republic of Korea (Zip code : 08501) Tel: +82-2-544-1436 Fax: +82-2-859-0045 Contact Us: inquiry@atid1.com www.atid1.com

