

# ATA802-BUS-B



### About ATA802-BUS-B RFID UHF Antenna

ATID's ATA802-BUS-B antenna is compact RFID UHF Antenna, circular polarization, and the working frequency band is 902MHz~928MHz. Careful design methodology achieves maximum efficiency and performance, withexcellent VSWR and axial ratios. It is ideal for many RFID applications such as smart retail, digital warehouse management, logistics management and other fields.

### **Application**


- Smart retail
- Digital warehouse management
- Logistics management and other fields

### **Features**

- Circular polarization
- High performance and high protection
- Beautiful appearance and light weight









## **Product Specifications**

#### **Performance Parameters**

Operating Frequency 902MHz~928MHz

VSWR ≤1.5:1 Input Impedance 50Ω Gain 5dBi

PolarizationCircular polarizationConnectorSMA-K type connectors

**HPBW** E:100 $^{\circ}$ , H:100 $^{\circ}$ 

**IP rating** IP65

#### **Environment**


Operating Temperature-40 °C to +85 °CStorage Temperature-40 °C to +85 °CHumidity Range≤95 %RH

### **Physical Parameters**

**Size** 117.5x117.5x23.5 (mm)

Weight 0.16kg
Radome material Modified ASA

**Installation** Bracket mounting / Screw fastening











ATA802-BUS-B Type Antenna appearance dimension drawing







All Features and specifications described are subject to change without notice.

